


▶ D/MS Series A/B Type Ordering Information

D/MS3102A18-10PY (62)

Connector Style
D/MS3100A Wall Mount Receptacle  (12S ~ 36 Size)
D/MS3101A Cable Receptacle  (12S ~ 36 Size)
D/MS3102A Box Mount Receptacle  (10SL ~ 36 Size)
D/MS3106A Straight Plug  (10SL ~ 36 Size)
D/MS3106B Straight Plug (Split Backshell)  (12S ~ 36 Size)
D/MS3108B Right Angle Plug (Split Backshell)  (12S ~ 36 Size)

**Deviation**  
Omit : Silver Plated Contacts (Standard)  
(62) : Gold Plated Contacts (0.5 μ m AU over Ni)

**Alternate Insert Position**  
No letter is required for normal position. The alternate insert positions, W, X, Y and Z, are available. W, X, Y and Z designate that an insert is rotated in its shell from the standard position. For detailed alternate insert positions, refer to page 8



**Contact Type**  
P : Pin Contact  
S : Socket Contact  
When a receptacle connector has pin contacts (P), its mating plug connector should have socket contacts(S). Reverse style of contacts is also feasible.

**Shell Size**  
Shell sizes are designated by the screw size of mating part which is described in inches multiply by 16. (e.g.) When the screw size of mating part is 1 1/8-18, it is 1 1/8 X 16 =18 of which shell size is 18.  
  
(Available shell size) :  
10SL, 12S, 14S, 16S, 16, 18, 20, 22, 24, 28, 32 and 36.

**Insert Arrangement**  
This is the number allocated to each shell size respectively with its sequential number beginning from number one(1). (However, there are the numbers which are not used.) The insert arrangement number does not show the number of contacts. For example on the insert arrangement 18-10: 18 shows the shell size. 10 shows the insert arrangement. (The number of contacts is 4.) With regard to the insert arrangement, refer to page 4 to page 7.