

Coaxial Cable G_02232

Description

PE-50 Ohm - single screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Strand-07	0.49 mm
Dielectric	PE (Polyethylene)		1.5 mm
Outer conductor	Copper	Braid, 96%	2 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	2.8 mm +/- 0.1

Print: HUBER+SUHNER G 02232 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	1 GHz
Capacitance	101 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MQm
Min. screening effectiveness	≥ 40 dB (up to 1 GHz)
Max. operating voltage	≤ 1.5 kV _{rms} (at sea level)
Test voltage	3 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	1.4 kg/100 m
Min. bending radius	static repeated (for ≤ 50 bendings)
	15 mm 28 mm

Environmental Data

Temperature range	-25 °C... +85 °C
Installation temperature	-20 °C... +60 °C
2011/95/EC (RoHS)	compliant

Additional Information

Ordering Information

Order as G_02232

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group U2 2 mm / 50 Ohm

Coaxial Cable G_02232

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.867

b = 0.1289

f_{max} = 1

P at 1GHz = 38

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0.05	0.2	0.061	170
0.1	0.29	0.087	120
0.15	0.36	0.108	98
0.2	0.41	0.126	85
0.25	0.47	0.142	76
0.3	0.51	0.157	69
0.35	0.56	0.170	64
0.4	0.6	0.183	60
0.45	0.64	0.195	57
0.5	0.68	0.206	54
0.55	0.71	0.218	51
0.6	0.75	0.228	49
0.65	0.78	0.239	47
0.7	0.82	0.249	45
0.75	0.85	0.258	44
0.8	0.88	0.268	42
0.85	0.91	0.277	41
0.9	0.94	0.286	40
0.95	0.97	0.295	39
1.0	1.0	0.304	38