


## Adjustable Low Dropout Regulator w/Reverse Current Protection

### ■ GENERAL DESCRIPTION

The NJM11100 is a 240mA output low dropout adjustable type voltage regulator. The available setting voltage range is very wide from 1.3V to 17V. This product has Reverse Current Protection without external SBD. Advanced Bipolar technology achieves low noise, high ripple rejection and high supply voltage. It is suitable for various applications such as car AVN, any consumer products and so on.

### ■ PACKAGE OUTLINE



NJM11100F1




NJM11100KH1

### ■ FEATURES


- Output Voltage Setting Range 1.3V to 17V
- Reference Voltage Accuracy 1.25V  $\pm$ 1.0%
- Output Current 240mA (min.) 320mA (typ.)
- Correspond to Low ESR capacitor (MLCC) 1.0 $\mu$ F: ( $V_o \geq 1.4V$ )
- Low Dropout Voltage 0.2V (typ.) @ $I_o=200mA$
- Input Voltage Range 2.1V to 18V
- ON/OFF Control
- Reverse Current Protection Circuit
- Thermal Shutdown Circuit
- Over Current Protection Circuit (OCP)
- Bipolar Technology
- Direct Replacement to TK11100 (180 degree rotated)
- Package Outline SOT-23-6-1, DFN6-H1(ESON6-H1)

### ■ PIN CONFIGURATION



Should be noted the device direction when replacing from TK11100.


1. CONTROL
2. GND
3. Noise Bypass
4.  $V_{OUT}$
5.  $V_{ADJ}$
6.  $V_{IN}$



1.  $V_{IN}$
2.  $V_{ADJ}$
3.  $V_{OUT}$
4. Noise Bypass
5. GND
6. CONTROL

Exposed Pad(Rear PAD) should be connect to GND

### ■ BLOCK DIAGRAM



# NJM11100

## ■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	MAXIMUM RATING	UNIT
Input Voltage	V <sub>IN</sub>	-0.3 to +20	V
Output Voltage	V <sub>OUT</sub>	-0.3 to +19	V
Control Pin Voltage	V <sub>CONT</sub>	-0.3 to +20	V
Output Adjust Pin Voltage	V <sub>ADJ</sub>	-0.3 to +4	V
Noise Bypass Pin Voltage (*5)	V <sub>NB</sub>	-0.3 to +4	V
Power Dissipation	P <sub>D</sub>	SOT-23-6	510(*1) 710(*2)
		DFN6-H1 (ESON6-H1)	450(*3) 1200(*4)
Operating Temperature Range	Topr	-40 to +85	°C
Storage Temperature Range	Tstg	-40 to +150	°C

(\*1): Mounted on glass epoxy board. (76.2×114.3×1.6mm: based on EIA/JDEC standard, 2Layers)

(\*2): Mounted on glass epoxy board. (76.2×114.3×1.6mm: based on EIA/JDEC standard, 4Layers), internal Cu area: 74.2×74.2mm

(\*3): Mounted on glass epoxy board (101.5×114.5×1.6mm: based on EIA/JEDEC standard, 2Layers FR-4, with Exposed Pad)

(\*4): Mounted on glass epoxy board (101.5×114.5×1.6mm: based on EIA/JEDEC standard, 4Layers FR-4, with Exposed Pad)

(4Layers: Applying 99.5×99.5mm inner Cu area and a thermal via hole to a board based on JEDEC standard JESD51-5)

(\*5): When input voltage is less than +4V, the absolute maximum control voltage is equal to the input voltage.

## ■ RECOMMENDED OPERATING CONDITIONS

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Voltage Range	V <sub>IN</sub>		2.1	-	18	V
Output Voltage Range	V <sub>OUT</sub>		1.3	-	17	V



## ■ ELECTRICAL CHARACTERISTICS

(Unless other noted, V<sub>IN</sub>=4V, R1=51kΩ, R2=68kΩ, C<sub>IN</sub>=0.1μF, C<sub>O</sub>=1.0μF (V<sub>O</sub><1.4V: 2.2μF), C<sub>p</sub>=0.01μF, C<sub>fb</sub>=100pF, Ta=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Reference Voltage	V <sub>ref</sub>	I <sub>O</sub> =30mA	-1.0%	1.25	+1.0%	V
Quiescent Current	I <sub>Q</sub>	I <sub>O</sub> =0mA, except I <sub>cont</sub>	-	200	260	μA
Quiescent Current at OFF-state	I <sub>Q(OFF)</sub>	V <sub>CONT</sub> =0V	-	-	100	nA
Ground Current	I <sub>GND</sub>	I <sub>O</sub> =50mA	-	0.75	1.5	mA
Output Current	I <sub>O</sub>	V <sub>O</sub> =0.3V	240	320	-	mA
Line Regulation	ΔV <sub>O</sub> /ΔV <sub>IN</sub>	V <sub>IN</sub> =V <sub>O</sub> +1V to V <sub>O</sub> +6V, I <sub>O</sub> =30mA	-	-	0.10	%/V
Load Regulation	ΔV <sub>O</sub> /ΔI <sub>O</sub>	I <sub>O</sub> =0 to 200mA	-	-	0.01	%/mA
Dropout Voltage(*6)	ΔV <sub>LO</sub>	I <sub>O</sub> =200mA	-	0.2	0.35	V
Control Voltage at ON-state	V <sub>CONT(ON)</sub>		1.6	-	-	V
Control Voltage at OFF-state	V <sub>CONT(OFF)</sub>		-	-	0.6	V
Control Current	I <sub>CONT</sub>	V <sub>CONT</sub> =1.6V	-	3	12	μA
Ripple Rejection	RR	e <sub>in</sub> =200mVrms, f=1kHz, I <sub>O</sub> =10mA, V <sub>O</sub> =3V setting	-	75	-	dB
Average Temperature Coefficient of Output Voltage	ΔV <sub>O</sub> /ΔTa	Ta=0°C to +85°C, I <sub>O</sub> =30mA	-	±35	-	ppm/°C
Output Noise Voltage	V <sub>NO</sub>	f=10Hz to 80kHz, I <sub>O</sub> =10mA, V <sub>O</sub> =3V setting	-	30	-	μVrms


(\*6): Except setting Output Voltage less than 2.1V.

## POWER DISSIPATION vs. AMBIENT TEMPERATURE



# NJM11100


## ■ TEST CIRCUIT



(\*7):  $V_O < 1.4\text{V}$ :  $2.2\mu\text{F}$


## ■ TYPICAL APPLICATION

1. In the case where ON/OFF Control is not required:



Connect CONTROL pin to  $V_{IN}$  pin  
 (\*8):  $V_O < 1.4V$ :  $2.2\mu F$

2. In use of ON/OFF CONTROL:



State of CONTROL pin:

- “H” → output is enabled.
- “L” or “open” → output is disabled.

(\*9):  $V_O < 1.4V$ :  $2.2\mu F$

[Output voltage setting formula]

$$V_{OUT} = V_{ref} \times \frac{R1 + R2}{R1}$$

$$V_{ref(typ)} = 1.25V$$

$$1.3V \leq V_{OUT(typ)} \leq 17.0V$$

R1 value should be selected between  $1k\Omega$  and  $120k\Omega$ .

## \* Input Capacitor $C_{IN}$

Input Capacitor  $C_{IN}$  is required to prevent oscillation and reduce power supply ripple for applications when high power supply impedance or a long power supply line.

Therefore, use the recommended  $C_{IN}$  value (refer to conditions of ELECTRIC CHARACTERISTIC) or larger and should connect between GND and  $V_{IN}$  as shortest path as possible to avoid the problem.

## \* Output Capacitor $C_O$ (MLCC)

Output capacitor ( $C_O$ ) will be required for a phase compensation of the internal error amplifier.

The capacitance and the equivalent series resistance (ESR) influence to stable operation of the regulator.

Use of a smaller  $C_O$  may cause excess output noise or oscillation of the regulator due to lack of the phase compensation.

On the other hand, Use of a larger  $C_O$  reduces output noise and ripple output, and also improves output transient response when rapid load change.

Therefore, use the recommended  $C_O$  value (refer to conditions of ELECTRIC CHARACTERISTIC) or larger and should connect between GND and  $V_{OUT}$  as shortest path as possible for stable operation

The recommended capacitance depends on the output voltage rank. Especially, low voltage regulator requires larger  $C_O$  value.

In addition, you should consider varied characteristics of capacitor (a frequency characteristic, a temperature characteristic, a DC bias characteristic and so on) and unevenness peculiar to a capacitor supplier enough.

When selecting  $C_O$ , recommend that have withstand voltage margin against output voltage and superior temperature characteristic though this product is designed stability works with wide range ESR of capacitor including low ESR products.

## \* Noise bypass Capacitor $C_p$

Noise bypass capacitor  $C_p$  reduces noise generated by band-gap reference circuit. Noise level and ripple rejection will be improved when larger  $C_p$  is used. Use of smaller  $C_p$  value may cause oscillation.


Use the  $C_p$  recommended value larger (refer to conditions of ELECTRIC CHARACTERISTIC) to avoid the problem.

## \* Reverse Current Protection





NJM11100 is built in Reverse Current Protection circuit.

So external Schottky barrier diode(SBD) is not required that this circuit prevents the large reverse current due to the output voltage being higher than the input voltage.






## CHARACTERISTICS



$V_{OUT}=1.3V$ :  $C_O=2.2\mu F$ ,  $R_1=51k\Omega$ ,  $R_2=2k\Omega$   
 $3.0V$ :  $C_O=1.0\mu F$ ,  $R_1=51k\Omega$ ,  $R_2=68k\Omega$   
 $17V$ :  $C_O=1.0\mu F$ ,  $R_1=51k\Omega$ ,  $R_2=640k\Omega$




## CHARACTERISTICS












## CHARACTERISTICS






V<sub>OUT</sub>=1.3V: C<sub>O</sub>=2.2μF, R<sub>1</sub>=51kΩ, R<sub>2</sub>=2kΩ  
 3.0V: C<sub>O</sub>=1.0μF, R<sub>1</sub>=51kΩ, R<sub>2</sub>=68kΩ  
 17V: C<sub>O</sub>=1.0μF, R<sub>1</sub>=51kΩ, R<sub>2</sub>=640kΩ



## CHARACTERISTICS




## CHARACTERISTICS




# NJM11100

## CHARACTERISTICS


Output Noise Voltage vs. Output Current




Output Noise Voltage vs. Output Current






Output Noise Voltage vs. Output Current








Output Noise Voltage vs. Noise Bypass Capacitance



## CHARACTERISTICS




## CHARACTERISTICS




## CHARACTERISTICS


Control Current vs. Ambient Temperature




Control Voltage vs. Temperature




Line Regulation vs. Ambient Temperature




Load Regulation vs. Ambient Temperature









Output Peak Current vs. Ambient Temperature



Thermal Shutdown Characteristic





## CHARACTERISTICS






## ■ CHARACTERISTICS



# NJM11100

## ■ PACKAGE OUT LINE

### SOT-23-6-1




#### NOTES

All linear dimensions are in millimeters.

UNIT : mm

DFN6-H1 (ESON6-H1)



UNIT : mm

NOTES

All linear dimensions are in millimeters.

[CAUTION]

The specifications on this datasheets are only given for information , without any guarantee as regards either mistakes or omissions.

The application circuits in this datasheets are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.