

### Mechanical Data

Item	Dimension	Unit
Module dimension	74.2 x 25.2	mm
Viewing area	61.0 x 15.1	mm
Dot Size	0.55 x 0.65	mm
Dot Pitch	0.60 x 0.70	mm

### Absolute Maximum Rating

Item	Symbol	Standard Value			Unit
		min.	typ.	max.	
Power Supply	VDD-VSS	3	3.3	5	V
Input Voltage	VI	0	---	VDD	V

Note: VSS=0 Volt, VDD=3.0/5.0 Volt.

### Electronical Characteristics

Item	Symbol	Condition	Standard Value			Unit
			min.	typ.	max.	
Input Voltage	VDD-VSS	—	3.0	3.3	5.0(bon=1 max=3.5V)	V
Supply Current	IDD	VDD=3.0V/5.0V	—	0.19	—	mA
Recommended LC Driving Voltage for Normal Temp. Version module	VDD-V0	-20°C	—	—	—	V
		25°C	—	4.5	—	
		+70°C	—	—	—	
LED Forward Voltage	VF	25°C	3.4	3.5	3.6	V
LED Forward Current	IF	25°C	28.8	32	50	mA

### Feature

1. 5x8 dots includes cursor
2. Built-in controller ST7032i
3. 3V/5V power supply
4. 1/16 duty cycle

Pin No.	Symbol	Description
1	VOUT	DC/DC voltage converter. Connect a capacitor between this terminal and VIN when the built-in booster is used.
2	CAP1N	For voltage booster circuit(VDD-VSS)
3	CAP1P	External capacitor about 0.1u-4.7uf
4	VDD	Power supply (+3.0 / 5.0v)
5	VSS	GND
6	SDA	(In I2C interface DB7 (SDA) is input data. SDA and SCL must connect to I2C bus (I2C bus is to connect a resistor between SDA/SCL and the power of I2C bus ).
7	SCL	(In I2C interface DB6 (SCL) is clock input. SDA and SCL must connect to I2C bus (I2C bus is to connect a resistor between SDA/SCL and the power of I2C bus ).
8	RST	RESET

COG type

## RX1602A3 COG 16x2 dots

### Dimension drawing

